

FICHA TÉCNICA VÁLVULA SEGURIDAD Fig. 328

CONEXIÓN	DN (mm)	TIPO	P. TARADO (Kg/cm ²)	CAUDAL (l/mi)	DIMENSIONES (mm)		
					A	B	C
R 1/4"	DN8 (Ø6mm)	3280604	4	1000	15	36	8
		3280606	6	1300			
		3280608	8	1575			
		3280610	10	1960			
		3280612	12	2550			
		3280615	15	3150			
R 3/8"	DN10 (Ø9mm)	3280904	4	1310	20	46	10
		3280906	6	1880			
		3280908	8	2450			
		3280910	10	3150			
		3280912	12	4080			
		3280915	15	5040			
R 1/2"	DN15 (Ø12mm)	3281204	4	1865	22	58	8,5
		3281206	6	2855			
		3281208	8	3850			
		3281210	10	5040			
		3281212	12	6700			
		3281215	15	8400			
R 3/4"	DN20 (Ø17mm)	3281704	4	2380	27	88	13
		3281706	6	3730			
		3281708	8	5180			
		3281710	10	6860			
		3281712	12	9350			
		3281715	15	11900			
R 1"	DN25 (Ø25mm)	3282504	4	2620	34	88	13
		3282506	6	4170			
		3282508	8	5740			
		3282510	10	7910			
		3282512	12	11250			
		3282515	15	14700			

